MENTOR
WATER TECHNOLOGIES USA

The Next Generation of Legionella & Waterborne Pathogen Protection for Healthcare Facilities

FDA 510(k)-Cleared • Class II Medical Device • EPA-Registered Establishment • Log 10 • ASTM F838-2020 Tested • NSF P376 • ASSE 2011-2022 • EPA WaterSense Approved

Hospitals & Medical Centers | Oncology & Transplant Units | NICU | Surgical & Acute Care | VA Medical Centers | ICU & Critical Care



Why Healthcare Facilities Chooses Mentor

- **FDA 510(k)-cleared**. **Class II** medical device
- Advanced **Protection.** Lower Operating **Cost.**
- Immediate Patient **Protection.**
- **150-180** Day Service Life.
- Industry-Leading Certified **Performance.**
- No **Chemicals**. No Daily **Maintenance.**
- Supports **Water Management** Programs.

8-18K
U.S. hospitalizations from Legionnaires' disease annually
Source: CDC Surveillance Data

25-40%
Fatality rate in high-risk and immunocompromised patients
Source: CDC Surveillance Data

Log 10
99.99999999% Bacterial Reduction
Source: ASTM F838-20 / IAPMO

150-180 days
Extended filter service life. Lower maintenance costs
Source: MWT Testing

Water Safety Solutions for Every Healthcare Application

PurGuard 360®

Handheld shower filter · POU
Model QF10-202/MWT-2740/2920

- FDA 510(k)-Cleared. Class II Medical Device
- 0.08 µm pore size
- Log 10 bacterial reduction (ASTM F838-2020)
- 150-180 days service life
- EPA-Watersense version available
- Available in 7 cm & 15 cm White or Chrome
- Tool-free install in under 5 min

ASTM F838-2020 · NSF P376 · ASSE 2011-2022
EPA WaterSense · FDA Est. #10094411. EPA FIFRA #105402-NLD-1

TapTech Pro®

Faucet/sink filter · POU
Model QF10-202/MWT-4250

- FDA 510(k)-cleared. Class II medical device
- 0.08 µm pore size
- Log 10 bacterial reduction (ASTM F838-2020)
- Up to 180-day service life
- EPA-WaterSense version available
- Tool-free install in under 5 min

ASTM F838-2020 · NSF P376 · ASSE 2011-2022
EPA WaterSense · FDA Est. #10094411. EPA FIFRA #105402-NLD-1

SkyStream®

Mounted/ceiling showerhead · POU
Model QF10-177/MWT-3100

- 0.08 µm pore size
- Log 10 bacterial reduction (ASTM F838-2020)
- Up to 135-day service life
- 4 spray modes · ADA compatible
- Tool-free install in under 5 min

ASTM F838-2020 · NSF P376 · ASSE 2011-2022
EPA WaterSense · FDA Est. #10094411. EPA FIFRA #105402-NLD-1



Protect Every High-Risk Water Outlet

A complete facility-wide point-of-use strategy without replacing existing plumbing infrastructure.



TapTech Pro®

Patient Room Sinks

Splash-back at sink level is a documented transmission pathway during face washing and oral care routines.

TapTech Pro® installs directly onto standard faucet threads in seconds.

Recommended for:

- Patient Room & Bathroom sinks
- Handwashing Stations
- Treatment Room Sinks
- Nursing Station Sinks
- Staff handwashing stations
- Clinical sinks

PurGuard 360®

Patient Room Showers

Patient showers generate aerosols, making them the highest-risk exposure point for Legionnaires' disease and other waterborne pathogens.

PurGuard 360® install in minutes on standard shower arms without plumbing modifications.

Recommended for:

- Patient Shower Rooms / Bathrooms
- Therapy & Rehabilitation Showers
- Assisted-Bathing Rooms
- Isolation-Room Bathrooms
- Common/Staff Showers



SkyStream®

Patient Room Showers

Patient showers generate aerosols, making them the highest-risk exposure point for Legionnaires' disease and other waterborne pathogens.

SkyStream® install in minutes on standard shower arms without plumbing modifications.

Recommended for:

- Patient Shower Rooms / Bathrooms
- Therapy & Rehabilitation Showers
- Assisted-Bathing Rooms
- Isolation-Room Bathrooms
- Common/Staff Showers

When a Waterborne Pathogen Is Detected, the First 24 Hours Matter

Patient Safety

Deploy Mentor's certified point-of-use filtration within minutes to immediately protect patient showers, faucets, and other high-risk water outlets while reducing exposure to Legionella and waterborne pathogens.

Regulatory Response

Mentor's FDA 510(k)-cleared Class II medical device filtration provides an immediate corrective measure, supporting your water management program with independently tested performance and documented action during regulatory investigations and inspections.

Continuity of Care

Mentor products install in minutes without replacing existing plumbing, helping facilities maintain patient care, minimize operational disruption, and continue normal operations while long-term remediation is completed.



(800) 259-9107

24/7 Support line: (307) 269-5900

info@mwt-us.com

www.mwt-us.com

1309 Coffeen Ave, Sheridan WY 82801

Confirmed Legionella Case?
Same-Day Shipment
Emergency Products In Stock
Nationwide Rapid Deployment

Purchase orders are not enough when a public health notice is issued. Installed, FDA and ASTM documented point-of-use filtration is an auditable corrective measure, in under 5 minutes per fixture.